

## Product Focus • Customer Commitment • Performance Flexibility

# NAXAN® EB123X

**Product Data Sheet** 

## ALKYL NAPHTHALENE SULFONIC ACID

**Description:** Catexel Nease LLC offers a few products from within our NAXAN® product

line that are used in oil filed applications. These emulsion breaker products are used

in enhanced oil recovery systems to resolve emulsions caused during the extraction

CAS # and processing of crude oil.

SECRET NAXAN® EB123X is a diisopropyl naphthalene sulfonic acid. It is similar to our

NAXAN® EB123 with xylene added to lower viscosity.

Typical Properties: Appearance Black viscous liquid

Density  $1.05 \text{ g/cm}^3$ 

pH < 2

**Product** 

**Specifications:** Property Specification

 Activity (%)
 45.0-55.0%

 Sulfuric acid (%)
 5.0 Maximum

 Water
 5.0 maximum

 Unsulfonated Oil (%)
 35.0-45.0%

**Applications:** Oilfield emulsion breaker

**Storage and** Store covered in a dry, well ventilated area. Keep container tightly closed when not in use.

Handling:

**Availability:** Bulk, 530 pound drums, 2,500 pound totes

**Chemical Control** This product is in compliance with the inventory listing requirements of the Chemical Control

Laws in the following countries: United States of America

**Transport Regulations** 

Shipping Description: Flammable Liquid, Corrosive n.o.s. (alkylnaphthalene sulfonic acid, sulfuric acid, xylene)
Hazard Class: 3 (8) ID Number: UN2924 Packing Group: II Label: Flammable, Corrosive

### **Catexel Nease LLC**

9774 Windisch Road, West Chester OH 45069 Customer Service 888-762-7373 www.catexel.com

#### Limited Warranty

The products sold by Catexel Nease LLC ("Seller") shall conform to the Seller's current published specifications. Seller makes no other warranty, express or implied, including warranty of merchantability or fitness for particular use, whether product is used singly or in combination with other substances or in any process. Nothing contained herein should be considered as a recommendation for use of any product or method in violation of any valid patent now effective or which may issue hereafter. Prior testing for fitness for use and compliance with all applicable statues by the user is a strict condition on the sale of any and all of Seller's products.