

Product Focus • Customer Commitment • Performance Flexibility

NAXCAT® MOD ACID 35 | Product Data Sheet

SULFONIC ACID BLEND, TSA/XSA

Description: Catexel Nease LLC manufactures a wide range of aromatic sulfonic acids. Aromatic sulfonic

> acids are made by sulfonating aromatic compounds with sulfuric acid, SO₃ or Oleum. They are comparable in strength to mineral acids such as sulfuric acid, but are especially suitable for organic

CAS# Mixture

reactions where an inorganic, mineral acid could cause charring, oxidation, or an unwanted

chemical reaction.

Naxcat® MOD ACID 35 is a lower water concentration version of NAXCAT® MOD ACID. It is a TSA/XSA blend. The blend of acids promotes low freezing temperature for ease of handling while maintaining a high degree of acidity.

Typical Properties: Appearance Amber to Brown Liquid

> рΗ < 1 Specific Gravity @ 25°C 1.3 Flash Point, °F > 200Molecular weight 175 Melting Point, °C 0 - 15

Solubility in water Approx. 67g/100ml

Crystallization range, °C

Specification **Product Specifications: Property**

> Active, % 92.0 min. Water Insolubles, % 4.0 max. Hydrocarbons, % 1.5 max. Water, % 1.0 max. Sulfuric Acid, % 2.0 max

Applications: Industrial cleaners, Textile Dye Manufacture, Polymers & Coatings Catalyst, Oilfield Applications

Keep container tightly closed when not in use. Store in cool, well ventilated area. Steel is corroded by Storage and

Handling: sulfonic acids and is not recommended for prolonged storage at elevated temperatures since iron and color

contamination could result. Dilution with water may increase corrosivity of the acid. Material will absorb

moisture.

Availability: Bulk, 575 pound drums, 2,750 pound totes

Chemical Control All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act

Law Status: (TSCA) Chemical Substance Inventory.

Transport Regulations

Shipping Description: Aryl sulfonic acids, liquid with not more than 5 percent free sulfuric acid

(Toluenesulfonic acid/Xylenesulfonic acid)

Hazard Class: 8 ID Number: UN2586 Packing Group: III Label: Corrosive

Catexel Nease LLC

9774 Windisch Road, West Chester OH 45069 Customer Service 888-762-7373 www.catexel.com

Limited Warranty

The products sold by Catexel Nease LLC ("Seller") shall conform to the Seller's current published specifications. Seller makes no other warranty, express or implied, including warranty of merchantability or fitness for particular use, whether product is used singly or in combination with other substances or in any process. Nothing contained herein should be considered as a recommendation for use of any product or method in violation of any valid patent now effective or which may issue hereafter. Prior testing for fitness for use, and compliance with all applicable statues by the user is a strict condition on the sale of any and all of Seller's products.