

Product Focus • Customer Commitment • Performance Flexibility

NAXAN® EB123X

Product Data Sheet

ALKYL NAPHTHALENE SULFONIC ACID

Description: Nease Co. LLC offers a few products from within our NAXAN® product line

that are used in oil filed applications. These emulsion breaker products are used in

enhanced oil recovery systems to resolve emulsions caused during the extraction and

<u>CAS #</u> processing of crude oil.

SECRET NAXAN® EB123X is a diisopropyl naphthalene sulfonic acid. It is similar to our

NAXAN® EB123 with xylene added to lower viscosity.

Typical Properties: Appearance Black viscous liquid

Density 1.05 g/cm^3 + 2 pH $+ 2 \text{ mg/s}^3$

Product

Specifications: Property Specification

Activity (%) 45.0-55.0% Sulfuric acid (%) 5.0 Maximum Water 5.0 maximum Unsulfonated Oil (%) 35.0-45.0%

Applications: Oilfield emulsion breaker

Storage and Store covered in a dry, well ventilated area. Keep container tightly closed when not in use.

Handling:

Availability: Bulk, 530 pound drums, 2,500 pound totes

Chemical Control This product is in compliance with the inventory listing requirements of the Chemical Control Laws

Law Status: in the following countries: United States of America

Transport Regulations

Shipping Description: Flammable Liquid, Corrosive n.o.s. (alkylnaphthalene sulfonic acid, sulfuric acid, xylene) Hazard Class: 3 (8) ID Number: UN2924 Packing Group: II Label: Flammable, Corrosive

Nease Co. LLC

9774 Windisch Road, West Chester OH 45069 Customer Service 888-762-7373 www.neaseco.com

Limited Warranty

The products sold by Nease Co. LLC ("Seller") shall conform to the Seller's current published specifications. Seller makes no other warranty, express or implied, including warranty of merchantability or fitness for particular use, whether product is used singly or in combination with other substances or in any process. Nothing contained herein should be considered as a recommendation for use of any product or method in violation of any valid patent now effective or which may issue hereafter. Prior testing for fitness for use and compliance with all applicable statues by the user is a strict condition on the sale of any and all of Seller's products.